



**Case A  
323.13**

**Model No. : 223 、 323 SERIES**
**Outline :**

- All series are liquid filled.
- All series are stainless steel products with water proof, and closed structures which are capable against acidity, alkalinity and corrosion. With the features of durability and accuracy, it is also good for long time running.
- Special materials of movement and bourdon tube have lasting durabilities.
- Specially it is applicable for corrosive fluid and strong fluctuation.

**Features :**

- Model** : 223 series. (Push Twist Removable Bezel-RB)  
323 series. (Crimped on Bezel-CB)
- Type** : Pressure gauge, Vacuum gauge, Compound gauge.
- Nominal Size** : 60mm.
- Case** : Stainless steel AISI 304 supplied with LM, CBM, LBM mount type and blowout disk on the top.
- Tubing** : Stainless steel AISI 316.
- Movement** : Stainless steel AISI 304.
- Connection** : Stainless steel AISI 304, 316, 1/4", 3/8", NPT, PT, PF.
- Pointer Type** : General (Selective Adjustable Pointer)
- Accuracy** : ± 1.5% F.S. (READ ANSI-B40.1 1985)
- Scale** : psi, bar, kPa, MPa, Kg/cm<sup>2</sup> etc. (Single or Dual Scale)

**Note :**

- LM : Lower Mount.
- CBM : Center Back Mount.
- LBM : Lower Back Mount.

**Specifications :**

Nominal size (mm)	Case	Connection	Model No.	Case Accessory	
60	A	NPT · PT · PF (1/4" · 3/8")	223.13	—	
			323.13	—	
	B		223.23	—	
			323.23	—	
	—		323.43	—	
			323.53	—	
	D		Front Flange	323.63	—
			323.73	—	
	Fixed Strap		323.83	L Clamps	
			323.93	U Bracket	

Ranges (Kg/cm <sup>2</sup> )	Socket	Tube	Accuracy (%F.S.)	Others
cmHg	S.S.304 S.S.316	S.S.316	± 1.5	· Case & Ring 304 St. St.  · Window Glass Acrylic (ASA LENS)  · Liquid Filled Glycerine Silicon
76				
cmHg				
1				
2				
3				
4				
6				
10				
15				
20				
0~				
1				
2				
3				
4				
6				
10				
15				
20				
25				
35				
50				
70				
100				
150				
250				
350				
500				
700				
1000				